SO2 Gas Sensor with Analog output AV10-G4-SO2

SKU: AV10-G4-SO2

Doc No: AV10-G4-SO2-DS-EN-10

Introduction

AV10-G4-SO2 is an electrochemical-type gas sensor with a high sensitivity to low concentrations of SO2 gas, high selectivity, and a stable baseline. It has built-in filter to remove effect from H2S and HCl. It is powered by a power supply of 15..36VDC and gives analog output 0-10VDC for easy integration.


- High accuracy and stability;
- Wide range of Power Supply;
- Filter & Protector;
- Plug & Play.

Typical Applications

Ambient Gas Monitoring in Facilities, Farm, Building, Factory, City...

- Indoor Air Quality monitoring;
- HVAC Control;
- Greenhouse;
- Smart Agriculture.
- Gas Leak Detector.





Specification

SENSOR SPECIFICATION	
Sensor type	Daviteq Seri-4 electrochemical gas sensor
Nominal range	0-100ppm
Resolution	0.1 ppm
Instability	+/- 0.1 ppm

T90 response time	< 20 s
Repeatability	< 2% of reading
Linearity	5% of full scale
Temperature compensation	Yes
Relative humidity range	15 % to 90 % RH non-condensing
Temperature range	-40 °C to 50 °C
Pressure range	Atmospheric ± 10%
Expected Operation Life	3-5 years in clean air
Expected Long-Term Output Drift in air	< 10 % of reading loss per year
Filter & Protector	Nylon filter
Sensor housing / Rating	Plastic / IP67
OTHER SPECIFICATION	
Output	0..10VDC
Power supply	15..36VDC, avg. < 100mA
Connector	M12-female 4-pin Code A
Housing	Thermal Plastic
Housing Rating	IP67 (electronics housing and connector)
Dimension	H138xD30
Net weight	<200 grams

CROSS SENSITIVITY DATA

The table below does not claim to be complete. Interfering gases should not be used for calibration.

Interfering Gas	Concentration (ppm)	Reading (ppm)
C2H4	100	0
CO	100	< 3
CS2	100	35
H2	100	< 1
H2S	20	0
NO	100	0
NO2	100	~ - 125

ORDERING CODE

Item code	Descriptions
AV10-G4-SO2-100-F	ANALOG OUTPUT 0-10VDC SO2 GAS SENSOR, 0-100PPM WITH FILTER, 15..36VDC SUPPLY, M12-F CONNECTOR
CALGAS-SO2-02	CALIBRATION CHARGES FOR GAS SENSOR, 2-POINT CALIBRATION

Please select below M12 cable with different lengths	
2M-MM12CAB4X0.25	M12 4PIN MALE ASSEMBLY CONNECTOR WITH SOLDERING TERMINALS AND CODING A AND CONTROL CABLE CU/PVC/OS/PVC 4X0.25MM2, L=2M, ROHS, SHIELD 80%
5M-MM12CAB4X0.25	M12 4PIN MALE ASSEMBLY CONNECTOR WITH SOLDERING TERMINALS AND CODING A AND CONTROL CABLE CU/PVC/OS/PVC 4X0.25MM2, L=5M, ROHS, SHIELD 80%
10M-MM12CAB4X0.25	M12 4PIN MALE ASSEMBLY CONNECTOR WITH SOLDERING TERMINALS AND CODING A AND CONTROL CABLE CU/PVC/OS/PVC 4X0.25MM2, L=10M, ROHS, SHIELD 80%

⚠ Link for full datasheet:

⚠ Link for manual:

Daviteq Technologies Inc

www.daviteq.com | info@daviteq.com

Revision #3
★ Created Mon, Oct 19, 2026 3:04 AM by Lộc Vĩnh Nguyễn
Updated Mon, Oct 19, 2026 3:12 AM by Lộc Vĩnh Nguyễn